

# Capacitance Meter

**HT-6013**

- Easy to read Large LCD display, 13mm
- Easily switch to 8 different measuring ranges from 0.1pF ~ 2000μF
- Use to measure capacitance of condensers, cables, switches, etc.



## SPECIFICATIONS

### GENERAL SPECIFICATIONS

Display	: 13mm LCD max. display 1,999
Measuring Range	: 200pf ~ 2,000μF, 8 ranges
Tuning/Adjustments	: 0 adjustment possible
Sampling Time	: 500ms
Battery	: 006P (9V) x 1 pc
Battery Life	: Approx. 100 hours
Operating Temp.	: 0 ~ +40°C
Operature Humidity	: 45 to 80% RH
Dimension	: 185(H) × 87(W) × 39(D)mm
Weight	: Approx. 310g. (Incl. Battery)
Accessories	: Instruction Manual x 1 pc. Spare Fuse x 1 pc. Test Alligator Clip (Red & Black) Battery x 1 pc.

### ELECTRICAL SPECIFICATIONS

Measuring Range	Max. Display	Resolution
200 pF	199.9 pF	0.1 pF
2 nF	1.999 nF	1 pF
20 nF	19.99 nF	10 pF
200 nF	199.9 nF	100 pF
2 μF	1.999 μF	1,000 pF
20 μF	19.99 μF	0.01 μF
200 μF	199.9 μF	0.1 μF
2,000 μF	1,999 μF	1 μF

Accuracy	: 0.5% Full Scale ±1d(200pF~200μF)
Excitation Voltage	: 2.8V, peak
Protection	: 0.2A / DC50V Fuse
Zero Adjust	: Limited to ±20pF

\* Specifications Subject to Change Without Prior Notice  
All Rights Reserved, Copyright © 2001 LINE SEIKI CO.,LTD.  
Last Revised: February 1, 2005 C6013-1

 **LINE SEIKI CO.,LTD**

37-7, CHUO-CHO 2-CHOME, MEGURO-KU, TOKYO, 152-0001 JAPAN  
Tel : +81-3-3716-5151 Fax : +81-3-3710-4552  
Email : sales@line.co.jp URL : http://www.line.co.jp